REPAIR, LEVELLING,
PROTECTION AND
FINISHING OF INDUSTRIAL,
RESIDENTIAL AND COMMERCIAL
FLOORINGS







TECHNICAL SOLUTION

DRIZORO S.A. has a wide range of flooring products with high performance and suitable for repair and patching, levelling, protection and decorative finishing of concrete surfaces at industrial, residential and commercial floors and pavements.

We provide patching and repair mortars with different ranges application thickness; cement-based or epoxy-cement based self-levelling mortars for adjustment of level tolerances or suitable for floors with temporary moisture barrier; fibre-reinforced mortars with increased abrasion resistance and limited concrete dusting, fast-setting mortars and self-levelling mortars for repair and restoration of floors. On the other hand, we provide protective and decorative top-coatings with easy cleaning and repair, high thermal resistance, high care standard and coloured aspect suitable against chemical attacks and wearing at chemical and pharmaceutical industry, processing areas (dry or wet), car parks (exterior and underground), offices and houses.







TECHNICAL ASSISTANCE

Our Sales Representatives and Technical Department composed of engineers and architects with wide experience in the construction industry, gives the most professional advice depending of the time available for the application and curing of the flooring systems, the design life, the operational requirements, the intended use and the surface design. Technical assistance includes an evaluation, diagnoses and the recommendation of the most suitable system, as well as the control during the application and the result.







REPAIR - LEVELLING - SCREEDING

with the state

An appropriate design and maintenance provides a long lasting for floorings but changes in the initial use lead a reduction in the expected life. For restoration of concrete floors, manufacturing facilities, highway and road, parking decks and ramps, **DRIZORO S.A**. provides a wide range of repair and patching mortars that offer high early strengths.

Levelling of uneven surfaces such as rough screeds, re-surfacing of floors to achieve a flat surface which will be covered with carpet, ceramic tiles or natural stone can be carried out using our cement or epoxy-cement based self-levelling flooring systems that have been formulated to be poured in place. Our epoxy-based self-levelling flooring systems provide a hygienic surface with high resistance to chemical attack and mechanical wearing: pharr maceutical, cosmetic, chemistry and food industries, laboratory areas, warehouses and commercial areas.











PROTECTION AND FINISHING

Mechanical strengths such as resistance to abrasion, toughness, durability and resilience, resistance to some aggressive chemicals, resistance to absorption of liquids and greases, suitability for cleaning and other aesthetic characteristics are factor influencing the selection of a top-coating.

DRIZORO S.A. cement-based, epoxy-based or polyurethanee based materials used as decorative and protective coatings fulfil the requirements regarding with the ambient conditions, uses and both mechanicals and chemical specifications: kitchens, hospitals, laboratories, food and beverage industry, marine environment, wastewater treatment plants, garages and manufacturing facilities.



DRIZORO, S.A.

Primavera 50-52, Parque Industrial Las Monjas 28850 TORREJÓN DE ARDOZ – MADRID (Spain)

Phone: (34) 91 676 66 76 - (34) 91 677 61 75 Fax: (34) 91 675 78 13

Technical Asistance 902 193 907

info@drizoro.com

www.drizoro.com